

Revision date:  
10.07.2018**Divinol Profi Lube SL****Article No.: 62301LK**

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

62301LK Divinol Profi Lube SL

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Grease

**1.3. Details of the supplier of the safety data sheet**

Company name:	Zeller+Gmelin GmbH & Co. KG	
Street:	Schlossstr. 20	
Place:	D-73054 Eisingen	
Telephone:	+49 (0) 7161 / 802-0	Telefax: +49 (0) 7161 / 802-290
e-mail:	info@zeller-gmelin.de	
Contact person:	Uwe Allmendinger	Telephone: +49 (0) 7161 / 802-297
e-mail:	produktsicherheit@zeller-gmelin.de	
Internet:	www.zeller-gmelin.de	
Responsible Department:	Produktsicherheit / Product Safety	

**1.4. Emergency telephone number:**Germany: +49 (0) 7161 / 802-400  
In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 - 08454 24 24 24 In Republic of Ireland: 01 809 2166**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane

**Signal word:** Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Revision date:  
10.07.2018

**Divinol Profi Lube SL**

**Article No.: 62301LK**

Page 2 of 8

**Precautionary statements**

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves.
P312	Call a POISON CENTER/doctor if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of this material and its container to hazardous or special waste collection point.

**2.3. Other hazards**

Without adequate ventilation, formation of explosive mixtures may be possible.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Mixture containing compressed gas.

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
	hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			10 - < 20 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
	hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			10 - < 20 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

When in doubt or if symptoms are observed, get medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

Revision date:  
10.07.2018**Divinol Profi Lube SL**  
**Article No.: 62301LK**

Page 3 of 8

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO<sub>2</sub>).**Unsuitable extinguishing media**

Full water jet.

**5.2. Special hazards arising from the substance or mixture**Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Do not inhale explosion and combustion gases.**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

See protective measures under point 7 and 8.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

See protective measures under point 7 and 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

**Advice on protection against fire and explosion**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition. Provide earthing of containers, equipment, pumps and ventilation facilities. Use non-sparking tools. Recommendation: Wear anti-static footwear and clothing

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Protect against: Frost. Keep away from heat. Protect against direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

**7.3. Specific end use(s)**

Observe technical data sheet.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

Revision date:  
10.07.2018

**Divinol Profi Lube SL**

**Article No.: 62301LK**

Page 4 of 8

### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

### 8.2. Exposure controls

#### Appropriate engineering controls

See chapter 7. No additional measures necessary.

#### Protective and hygiene measures

When using do not eat, drink, smoke, sniff.

#### Eye/face protection

Eye glasses with side protection.

#### Hand protection

Wear suitable gloves. Recommended glove articles: DIN EN 374. Suitable material: NBR (Nitrile rubber). Breakthrough time (maximum wearing time): > 120 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Skin protection

Protective clothing.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFA P / Full-/half-/quarter-face masks (DIN EN 136/140) + Combination filtering device (EN 14387), e.g. A P.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	yellowish	
Odour:	characteristic	
pH-Value:		not applicable

#### Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Pour point:	not determined
Flash point:	not applicable

#### Explosive properties

The product is: not explosive. Heating causes rise in pressure with risk of bursting. In use may form flammable/explosive vapour-air mixture.

Lower explosion limits:	not applicable
Upper explosion limits:	not applicable
Ignition temperature:	not determined
Decomposition temperature:	No information available.
Vapour pressure:	not determined
Density (at 15 °C):	0,92 g/cm <sup>3</sup>
Water solubility:	insoluble
Partition coefficient:	not determined

Revision date:  
10.07.2018**Divinol Profi Lube SL**  
**Article No.: 62301LK**

Page 5 of 8

Viscosity / dynamic:	not applicable
Viscosity / kinematic:	not applicable
Flow time:	not applicable
Vapour density:	not determined
Evaporation rate:	not determined

**9.2. Other information**

No information available.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

No hazardous reaction when handled and stored according to provisions.

**10.4. Conditions to avoid**

Heat.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

No information available.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

**Irritation and corrosivity**

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience****Other observations**

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

**SECTION 12: Ecological information****12.1. Toxicity**

There are no data available on the mixture itself.

**12.2. Persistence and degradability**

Revision date:  
10.07.2018

**Divinol Profi Lube SL**  
**Article No.: 62301LK**

Page 6 of 8

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

No data available

**12.6. Other adverse effects**

No data available

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Advice on disposal**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

**Waste disposal number of contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Contaminated packaging**

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0  
 Transport category: 2  
 Tunnel restriction code: D

**Marine transport (IMDG)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Marine pollutant: YES  
 Special Provisions: 63, 190, 277, 327, 344, 381, 959

Revision date:  
10.07.2018**Divinol Profi Lube SL**  
**Article No.: 62301LK**

Page 7 of 8

Limited quantity: 1000 mL  
Excepted quantity: E0  
EmS: F-D, S-U**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1Special Provisions: A145 A167 A802  
Limited quantity Passenger: 30 kg G  
Passenger LQ: Y203  
Excepted quantity: E0  
IATA-packing instructions - Passenger: 203  
IATA-max. quantity - Passenger: 75 kg  
IATA-packing instructions - Cargo: 203  
IATA-max. quantity - Cargo: 150 kg**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: HYDROCARBONS, C7

**14.6. Special precautions for user**

No data available

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; butane

2010/75/EU (VOC): 74,8 % (688,3 g/l)  
Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information: E2

**National regulatory information**

Water contaminating class (D): 2 - clearly water contaminating

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 3,7,8,9,13,14,15.

**Abbreviations and acronyms**

ADR: Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations

Revision date:  
10.07.2018**Divinol Profi Lube SL**  
**Article No.: 62301LK**

Page 8 of 8

concerning the International Carriage of Dangerous Goods by Rail)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organization  
CAS: Chemical Abstracts Service (a division of the American Chemical Society)  
DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
WEL (UK): Workplace Exposure Limits  
TWA (EC): Time-Weighted Average  
STEL (EC): Short Term Exposure Limit  
ATE: Acute Toxicity Estimate  
LD50: Lethal Dose, 50% (median lethal dose)  
LC50: Lethal Concentration, 50% (median lethal concentration)  
EC50: half maximal Effective Concentration  
ErC50: EC50 in terms of reduction of growth rate  
AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen  
VwVwS: Verwaltungsvorschrift wassergefährdende Stoffe

**Relevant H and EUH statements (number and full text)**

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**Further Information**

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

-----  
The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*