

Revision date:
05.03.2019**Multicor DW 3 Extra Light**

Article No.: 90500

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

90500 Multicor DW 3 Extra Light

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Corrosion protection agent

1.3. Details of the supplier of the safety data sheet

Company name:	Zeller+Gmelin GmbH & Co. KG	
Street:	Schlossstr. 20	
Place:	D-73054 Eislingen	
Telephone:	+49 (0) 7161 / 802-0	Telefax: +49 (0) 7161 / 802-290
e-mail:	info@zeller-gmelin.de	
Contact person:	Uwe Allmendinger	Telephone: +49 (0) 7161 / 802-297
e-mail:	produktsicherheit@zeller-gmelin.de	
Internet:	www.zeller-gmelin.de	
Responsible Department:	Produktsicherheit / Product Safety	

1.4. Emergency telephone number:Germany: +49 (0) 7161 / 802-400
In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 - 08454 24 24 24 In Republic of Ireland: 01 809 2166**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

May be fatal if swallowed and enters airways.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics

Signal word: Danger

Pictograms:

**Hazard statements**

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains sulfonic acids, petroleum, calcium salts, TBN < 300. May produce an allergic reaction.

2.3. Other hazards

Results of PBT and vPvB assessment: not applicable.

SECTION 3: Composition/information on ingredients

Revision date:
05.03.2019

Multicor DW 3 Extra Light
Article No.: 90500

Page 2 of 8

3.2. Mixtures
Chemical characterization

Hydrocarbon-based mixture.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
	hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics			25 - <= 100 %
	927-285-2		01-2119480162-45	
	Asp. Tox. 1; H304 EUH066			
111-76-2	2-Butoxy-ethanol			2.5 - < 5 %
	203-905-0	603-014-00-0	01-2119475108-36	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H332 H312 H302 H315 H319			
61789-86-4	Sulfonsäuren, Erdöl-, Calciumsalze, TBN < 300			0.3 - < 1 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunk in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures
5.1. Extinguishing media
Suitable extinguishing media

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO₂). Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Revision date:
05.03.2019

Multicor DW 3 Extra Light
Article No.: 90500

Page 3 of 8

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

SECTION 6: Accidental release measures
6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage
7.1. Precautions for safe handling
Advice on safe handling

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

Advice on protection against fire and explosion

No special measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect against direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol	urine	Post shift

Revision date:
05.03.2019

Multicor DW 3 Extra Light
Article No.: 90500

Page 4 of 8

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
111-76-2	2-Butoxy-ethanol			
Consumer DNEL, long-term		oral	systemic	3,2 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	44,5 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	89 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	38 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	75 mg/kg bw/day
Consumer DNEL, acute		inhalation	local	123 mg/m ³
Worker DNEL, acute		inhalation	local	246 mg/m ³
Consumer DNEL, acute		inhalation	systemic	426 mg/m ³
Worker DNEL, acute		inhalation	systemic	663 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	49 mg/m ³
Worker DNEL, long-term		inhalation	systemic	98 mg/m ³

PNEC values

CAS No	Substance	Value
111-76-2	2-Butoxy-ethanol	
Freshwater		8,8 mg/l
Marine water		0,88 mg/l
Freshwater sediment		34,6 mg/kg
Marine sediment		3,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		463 mg/kg
Soil		3,13 mg/kg

8.2. Exposure controls
Appropriate engineering controls

See chapter 7. No additional measures necessary.

Protective and hygiene measures

When using do not eat, drink, smoke, sniff.

Eye/face protection

Eye glasses with side protection.

Hand protection

Wear suitable gloves. Recommended glove articles: DIN EN 374. Suitable material: NBR (Nitrile rubber). Breakthrough time (maximum wearing time): > 480 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Skin protection

Protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. When splashes or fine mist form, a permitted breathing apparatus suitable for these purposes must be used. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFA P / FFP3.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Revision date:
05.03.2019**Multicor DW 3 Extra Light**

Article No.: 90500

Page 5 of 8

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	yellow
Odour:	characteristic

pH-Value: not determined

Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: > 180 °C

Pour point: not determined

Flash point: > 61 °C EN ISO 2719

Lower explosion limits: 0,5 vol. %

Upper explosion limits: 5,0 vol. %

Ignition temperature: not determined

Decomposition temperature: No information available.

Vapour pressure: not determined

Density (at 20 °C): 0,79 g/cm³ DIN EN ISO 12185

Water solubility: insoluble

Partition coefficient: not determined

Viscosity / dynamic: not determined

Viscosity / kinematic:
(at 20 °C) 2,3 mm²/s ASTM D 7042

Flow time: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No information available.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Revision date:
05.03.2019

Multicor DW 3 Extra Light
Article No.: 90500

Page 6 of 8

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
111-76-2	2-Butoxy-ethanol				
	oral	LD50 mg/kg	470	Rat	
	dermal	ATE mg/kg	1100		
	inhalation vapour	ATE	11 mg/l		
	inhalation aerosol	ATE	1,5 mg/l		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains sulfonic acids, petroleum, calcium salts, TBN < 300. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways. (hydrocarbons, C 11-C14, isoalkanes, cyclics, <2% aromatics)

Practical experience
Other observations

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel.

SECTION 12: Ecological information
12.1. Toxicity

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
111-76-2	2-Butoxy-ethanol	0,81

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Advice on disposal

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

Revision date:
05.03.2019**Multicor DW 3 Extra Light**

Article No.: 90500

Page 7 of 8

Waste disposal number of waste from residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine pollutant:

NO

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC): 92 % (726,4 g/l)
Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,9,15.

Abbreviations and acronyms

ADR: Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations

Revision date:
05.03.2019

Multicor DW 3 Extra Light
Article No.: 90500

Page 8 of 8

concerning the International Carriage of Dangerous Goods by Rail)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 CAS: Chemical Abstracts Service (a division of the American Chemical Society)
 DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 WEL (UK): Workplace Exposure Limits
 TWA (EC): Time-Weighted Average
 STEL (EC): Short Term Exposure Limit
 ATE: Acute Toxicity Estimate
 LD50: Lethal Dose, 50% (median lethal dose)
 LC50: Lethal Concentration, 50% (median lethal concentration)
 EC50: half maximal Effective Concentration
 ErC50: EC50 in terms of reduction of growth rate
 AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen
 VwVwS: Verwaltungsvorschrift wassergefährdende Stoffe

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains sulfonic acids, petroleum, calcium salts, TBN < 300. May produce an allergic reaction.

Further Information

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)