

Technical Data Sheet

Divinol CAF

Product description

- Test oil for injection pumps according to ISO 4113-CV-AW
- mineral oil containing preparation of low viscosity
- high oxidation stability
- excellent corrosion protection
- outstanding wear protection characteristics

Manufacturer approval

Divinol CAF fulfills the requirements of the **Bosch standard VS 15665-OL** and **ISO 4113-CV-AW**.

Characteristics

Density/15°C / DIN EN ISO 12185:	824 kg/m ³
Viscosity/40°C / DIN 51 562:	2.52 mm ² /s
Flash point (Pensky-Martens) / DIN EN ISO 2719:	> 90 °C
Cloud point / DIN ISO 3015:	< -10 °C
Pour point / DIN ISO 3016:	< -20 °C
Initial boiling point / DIN 51 751:	210 °C
Final boiling point / DIN 51 751:	360 °C

Application

Divinol CAF is a low viscosity mineral oil with especially adjusted additives for final testing of diesel injection components.

2928V3

04/2017-2928V3-4

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1