



TECHNICAL DATA SHEET

Zubora 57 H Plus

Boron-free and long-term stable cooling lubricant

PRODUCT DESCRIPTION

- + semi-synthetic, water-miscible high-performance cooling lubricant
- + on the basis of mineral oil
- + free of boron
- + free of formaldehyde releasers
- + long-term stable
- + excellent corrosion protection
- + REACH-compliant substances
- + resistance of plastics as well as of paints and coatings according to VDI 3035

As the product does not contain any secondary amines, there is no risk of formation of nitrosamines according to the current state of knowledge.

As **Zubora 57 H Plus** is inhibited against the formation of nitrosamines no stable nitrosamines can be formed, even if there are any secondary amines and nitrites (e. g. due to external carry-over). Therefore, in case of exceeding the limit value for nitrite according to TRGS 611, it is not necessary to change the emulsion partially or completely.

CHARACTERISTICS

Density/15°C / DIN EN ISO 12185	980 kg/m ³
Viscosity/20°C / ASTM D 7042	114.5 mm ² /s
pH-value (5 % in H ₂ O) / DIN 51 369	9.6
Cast iron chips test (1:20) / DIN 51 360/T2	Corrosion degree 0
Mineral oil content	30 %

32020

08/2019-32020-0

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



TECHNICAL DATA SHEET

Zubora 57 H Plus

Boron-free and long-term stable cooling lubricant

Water hazard class, concentrate	2
Water hazard class, emulsion	(< 22,2%) 1
Correction factor for determination of the concentration - refractometer	1.5

APPLICATION

Zubora 57 H Plus can be used for cutting operations up to medium difficulty. Furthermore, it is well suited for grinding. Due to the special formulation **Zubora 57 H Plus** is particularly long-term stable.

It is suitable for machining of many materials from normal to hardened steel grades, aluminium or cast iron materials.

Zubora 57 H Plus is designed for use in hard water and shows special foaming characteristics with prepared water quality of more than 12° dH.

Recommended hardness of the preparation water:

12 to 24° dH.

WORKING CONCENTRATION

Cutting operations 5 - 8 %
Grinding 4 - 5 %

STORAGE

Recommended storage temperature: +5 °C up to max. +40 °C.

32020

08/2019-32020-0

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



TECHNICAL DATA SHEET

Zubora 57 H Plus

Boron-free and long-term stable cooling lubricant

MISCELLANEOUS

Zubora cooling lubricants and our guide and slide way oils **Divinol T 3 EP ISO 32 / Divinol T 6 EP ISO 68 / Divinol T 8 EP ISO 100 / Divinol T 12 EP ISO 220** are optimally compatible with each other. The combined use shows excellent de-emulsification properties, i.e. mixtures of emulsions and slide way oils separate quickly. Black stains can be excluded to a great extent.

If there are increased demands on **corrosion protection**, e. g. for external transport, we recommend our anti-corrosion agents containing hydrocarbons (**Multicor dewatering fluids**). They are optimally adapted to our water-miscible cooling lubricants.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

32020

08/2019-32020-0

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

3 / 3