## **Technical Data Sheet**

## **AL-Inhibitor**

## **Product description**

**AL-Inhibitor** is a diluted corrosion inhibitor for aluminium. This additive can be used in diluted solutions which are in contact with various aluminium surfaces. The use does not depend on the hardness of water. The characteristics of the product are normally not influenced by a small quantity of **AL-Inhibitor**.

1150 kg/m<sup>3</sup>

10 mm<sup>2</sup>/s

> 100 °C (DIN 51 376)

## Characteristics

Density/20°C / DIN EN ISO 12185 :

Viscosity/20°C / ASTM D 7042 :

Flash point:

Application

Addition of 0.1 % **AL-Inhibitor** into the used solution at the onset of bloom on the machined aluminium.

60200

04/2017-60200-5

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1/1



ZG Division: Industrial Lubricants Zeller+Gmelin GmbH & Co. KG Schlossstr. 20 D73054 Eislingen/Fils - Germany Tel. +49 7161 802-0 - Fax +49 7161 802-290 www.zeller-gmelin.de - info@zeller-gmelin.de

